

# TankSystem100L

A compact and adaptable tanking solution



Specifically designed to operate with the complete range of Micron shielded CDA and high flow machinery, the 100L Tank System offers uncompromising flexibility alongside enhanced productivity and spraying efficiencies.

- Incorporates both hand wash and flushing tanks
- Compact modular assembly
- Self contained pump, filter and agitation system
- Suitable for both CDA and high flow applications
- Front or rear 3 point linkage mounting without adaptation

## Modular construction

Specifically designed with flexibility in mind, the system allows for attachment of the complete range of Micron shielded CDA and high flow equipment. Intelligent positioning of attachment locations allows machinery to be positioned to suit individual operations, in a wide variety of combinations, mounted front or rear.

## Safe, efficient and cost effective

The modular design does not require the use of a PTO or hydraulics, just a single 12 volt (3 amp) electrical supply reducing operator risk of injury. Attaching the machine to a tractor is quick and easy, saving valuable time.

When used with CDA low volume machinery, the Tank System can further increase productivity through reducing filling time which means more time can be spent spraying.

## Built-in flushing and hand wash tanks

Alongside the 100 litre mixed chemical tank there are two separate 15 litre tanks carrying clean fresh water for rinsing the system and operator hand washing. Flushing the system out after spraying is as simple as turning a tap, with ample supply to thoroughly cleanse the main tank and any connected machinery of chemicals. All tanks are clearly identified to reduce the risk of contamination.

## High specification pumping and mixing

The pumping system contains the features that would be expected of any professional sprayer. All fluids are filtered and an agitation system ensures complete chemical mixing before spraying.



### Specification

<b>Mixed chemical tank capacity:</b>	100 litre
<b>Hand wash tank capacity:</b>	15 litre
<b>Flushing tank capacity:</b>	15 litre
<b>Power requirement:</b>	12 volt (3 amp)
<b>Vehicle mounting:</b>	3 point linkage: CAT 1 & 2, front or rear
<b>Flow rate:</b>	19 litre/minute Flojet® pump
<b>Max working pressure:</b>	2.5 bar
<b>Sprayer mounting positions:</b>	Left, right and centre
<b>Weight (empty):</b>	72kg
<b>Suitable for:</b>	CDA and high flow applications
<b>Suitable with the following Micron shielded sprayers:</b>	Undavina, Spraydome Varidome, Spraymiser
<b>Optional extras:</b>	Retractable parking stands Hard surface wheels Electric actuated folding

Distributed by